LP SERIES-General Purpose

LP2-350 (2V350AH)

Specification

Nomial Voltage	2V
Nomial Capacity(10HR)	350.0AH
Dimension	Length 170±2mm (6.69 inches) Width 150±2mm (5.91 inches) Container Height 328±2mm (12.91 inches) Total Height (with Terminal) 350±2mm (13.78 inches)
Approx Weight	Approx 19.0 kg (41.9lbs)
Terminal	T11
Container Material	ABS
Rated Capacity	368.0 AH/18.4A (20hr ,1.80V/cell,25°C/77°F) 350.0 AH/35.0A (10hr,1.80V/cell,25°C/77°F) 299.5 AH/59.9A (5hr,1.75V/cell,25°C/77°F) 262.5 AH/87.5A (3hr,1.75V/cell,25°C/77°F) 210.0 AH/210.0A (1hr,1.60V/cell,25°C/77°F)
Max. Discharge Current	2800A (5s)
Internal Resistance	Approx 0.8mΩ
Operating Temp.Range	Discharge : -15～50°C (5～122°F) Charge : 0～40°C (32～104°F) Storage : -15～40°C (5～104°F)
Nominal Operating Temp. Range	25±3°C (77±5°F)
Cycle Use	Initial Charging Current less than105.0A.Voltage 2.4V~2.5V at 25°C(77°F)Temp. Coefficient -5mV/°C
Standby Use	No limit on Initial Charging Current Voltage 2.25V~2.3V at 25°C(77°F)Temp. Coefficient -3mV/°C
Capacity affected by Temperature	40°C (104°F) 103% 25°C (77°F) 100% 0°C (32°F) 86%
Self Discharge	Leoch LP series batterys may be stored for up to 6 months at 25°C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.

Applications

- *Tele-communication central station (wired or cellular)*
- *Power system communication, military communication, etc.*
- *Network communication including: data transmission, television signal transmission, etc.*
- *Uninterruptable Power System (UPS- for Telecom)*

Constant Current Discharge (Amperes) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	408.4	359.8	316.3	280.0	234.0	190.0	155.1	104.0	79.5	64.1	54.8	48.2	39.1	33.4	17.7
1.80V/cell	\	421.0	360.4	313.8	257.1	204.4	165.2	109.4	86.1	66.2	57.1	50.3	41.0	35.0	18.4
1.75V/cell	\	482.5	407.7	347.7	279.7	221.2	177.8	116.0	87.5	69.9	59.9	52.7	42.0	35.7	18.6
1.70V/cell	\	\	450.7	382.4	303.9	236.3	188.2	122.5	91.4	72.8	62.3	54.5	43.4	36.6	19.0
1.65V/cell	\	\	479.5	404.2	318.4	245.6	195.6	126.5	94.3	75.0	64.0	55.5	44.2	37.2	19.3
1.60V/cell	\	\	\	450.7	348.3	265.7	210.0	132.8	98.2	78.1	67.0	58.0	45.9	38.4	19.9

Constant Power Discharge (Watts) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	746.6	664.6	590.1	527.7	446.0	365.3	299.2	216.3	163.2	127.8	107.5	97.4	78.2	67.0	35.2
1.80V/cell	\	768.6	663.5	582.8	482.5	389.8	317.0	228.2	170.3	133.0	111.3	100.8	81.0	69.2	36.3
1.75V/cell	\	866.6	741.4	639.7	520.5	417.9	339.6	240.3	178.2	139.0	116.4	105.3	84.5	71.7	37.5
1.70V/cell	\	\	808.0	698.2	562.5	444.7	358.3	252.7	186.1	144.7	120.9	109.3	87.6	74.3	38.7
1.65V/cell	\	\	853.1	732.4	584.5	458.1	369.7	258.8	190.1	148.0	123.8	111.7	89.1	75.5	39.4
1.60V/cell	\	\	\	807.7	634.9	492.9	394.8	274.9	200.0	155.0	129.1	116.1	92.8	79.0	41.0

Dimensions

T11 Terminal

Unit: mm [inches]









Discharge Characteristics



Float Charging Characteristics



Temperature Effects in Relation to Battery Capacity



Effect of Temperature on Long Term Float Life



Cycle Life in Relation to Depth of Discharge



Self Discharge Characteristics



A No supplementary charge required
(Carry out supplementary charge before use if 100% capacity is required.)

B Supplementary charge required before use.Optional charging way as below:
1.Charged for above 3 days at limted current 0.25CA and constant volatge 2.25V/cell.
2.Charged for above 20hours at limted current 0.25CA and constant volatge 2.45V/cell.
3.Charged for 8~10hours at limted current 0.05CA .

C Supplementary charge may often fail to recover the capacity.
The battery should never be left standing till this is reached.

Sales Office

China sales office:

Add:5th Floor,Xinbaohui Bldg.,Nanhai Blvd.,
Nanshan,Shenzhen, China. 518052
Tel:+ 86-755-86036060 (100 lines)
Fax: +86-755-26067269
E-mail:export@leoch.com
Http://www.leoch.com

North America sales office:

Add: 19751 Descartes, Unit A,
Foothill Ranch, CA 92610, USA
Tel: 949-588-5853
Fax: 949-588-5966
E-mail: sales@leoch.us
Http://www.leoch.us

Europe sales office:

Add: LaCampagna House. Main Road.
Gloucester. GL2-8JH. United Kingdom
Tel: +44(0) 1452 751016
E-mail: Sales.Europe@leoch.com
Http://www.leoch.com